



TAESUNG AUTOIND PVT LTD

#165, SIDCO INDUSTRIAL ESTATE, THIRUMAZHISAI, CHENNAI-600124.

Email: taesungautoind@yahoo.com

Material Safety Data Sheet (MSDS)

Product Name: ECO NON DRYING PASTE

Version: 1.0

Date of Issue: March 14, 2025

Section 1: Identification

Product Name: ECO NON DRYING PASTE

Use: Non drying multiple use

Manufacturer: TAESUNG AUTOIND PVT LTD

Emergency Contact: +91- 9600172742, 9600297494

Section 2: Hazard Identification

Classification:

- Skin Corrosion/Irritation: Category 1
- Eye Damage/Irritation: Category 1
- Acute Toxicity (Inhalation/Oral): Harmful

Signal Word: DANGER

Hazard Statements:

- Causes severe skin burns and eye damage
- Harmful if swallowed or inhaled

Precautionary Statements:

- Avoid contact with eyes, skin, and clothing
- Wear protective gloves, eye/face protection

- Use in a well-ventilated area

Section 3: Composition/Information on Ingredients

Chemical Name	CAS Number	Approximate %
Chlorinated Solvent	75-09-2	95 %
Phenol	108-95-2	2 %
Inhibitor	2516-92-9	3 %

Section 4: First-Aid Measures

Eye Contact: Flush with large amounts of cool water for at least 15 minutes. Seek medical attention immediately.

Skin Contact: Wash with plenty of water. Remove contaminated clothing.

Inhalation: Move to fresh air. Get medical attention if symptoms persist.

Ingestion: Rinse mouth with water. Drink water followed by milk or milk of magnesia. Do not induce vomiting. Seek immediate medical attention.

Section 5: Fire-Fighting Measures

Flash Point: None

Suitable Extinguishing Media: Use media appropriate for surrounding fire (product is non-flammable)

Hazardous Decomposition Products: May release toxic vapors upon combustion

Section 6: Accidental Release Measures

Personal Precautions: Wear appropriate PPE (gloves, goggles). Ensure adequate ventilation.

Spill Cleanup: Neutralize with acidic material, dilute, and dispose per local regulations. Avoid runoff to water sources.

Section 7: Handling and Storage

Handling: Avoid contact with skin, eyes, and clothing. Use in well-ventilated areas.

Storage: Store in closed containers between 5–40°C. Keep away from heat sources.

Section 8: Exposure Controls/Personal Protection

Engineering Controls: Ensure good ventilation.

Personal Protective Equipment (PPE):

- Eyes: Safety goggles
- Skin: Chemical-resistant gloves
- Respiratory: Use in well-ventilated area; respirator if needed

Section 9: Physical and Chemical Properties

Appearance: Light to reddish brown wax-layered liquid

Odor: Characteristic

Specific Gravity @ 25°C: 1.22 ± 0.01

Flash Point: None

Solubility: Not specified

pH: Alkaline

Section 10: Stability and Reactivity

Reactivity: Stable under normal conditions

Incompatible Materials: Avoid use in aluminum or zinc pressure systems

Hazardous Decomposition: May produce toxic vapors when heated

Section 11: Toxicological Information

Acute Effects:

- Skin/Eye: Severe irritation/burns
- Inhalation/Oral: Harmful

Chronic Effects: Not specified

Section 12: Ecological Information

Environmental Impact: Not evaluated. Avoid environmental release.

Section 13: Disposal Considerations

Disposal Method: Neutralize with acid, dilute, and dispose in compliance with local regulations.

Section 14: Transport Information

UN Number: [TBD]

Proper Shipping Name: Paint Remover (Non-flammable)

Packing Group: [TBD]

Hazard Class: [TBD]

Shipping Method: Can be shipped via any common carrier

Section 15: Regulatory Information

Complies with local chemical safety regulations. Confirm region-specific details (REACH, OSHA, etc.).

Section 16: Other Information

Shelf Life: 1 year

Revision Date: March 14, 2025

Disclaimer: Based on available data believed to be reliable. No guarantee or liability accepted for conditions outside the company's control.